

FertiMAX

Fertilizer applicator gang
for sugar cane

PRO



Fertilizing your cane in the right spot!



Weight: 160 kg

Discs
- smooth 28"
- notched 29.5"

Running
forward

Robust
with 1 1/4 arm

Stainless steel
unloading tube

Discs cleaning
system

Application deep: 7 a 12cm

Fertilizer applicator gang for sugar cane.

FertiMAX PRO

Fertilizer for sugar cane with 4 FertiMAX gangs (optional 3 and/or 2), plastic fertilizer hopper, distribution system with auger and three dosage control options.

Simple and agile equipment, 3-point hitch to the tractor, requiring low power. Suitable for all solid fertilizers, incorporates and maintains the fertilizer protected even with a high trash blanket on the surface.

Protect the fertilizer

The depth achieved by the equipment guarantees optimal protection, in such a way that the fertilizer is incorporated into the soil avoiding its volatilization, also protected from fires whilst starting its effect immediately, being an optimal option for the use of urea.



Versatile

- Working capacity with a wide speed range.
- Adjust to different space configurations.
- More than one dosage thread option.

Features

Height:	2,5 m
Width:	3.0 m (possible extension 3.6 m)
Weight:	1350 kg
Fertilizer type:	Solid
Fertilizer load:	1000 kg
Fertilizer regulation (* 1):	Valv. Manual
Depth of application:	~7 a 12 cm
Line spacing:	1,10 a 1,50 m
Speed (max):	12 km/h
FertiMAX bodies:	4 / 3 / 2
Tractor power:	120 hp
Coupling to the tractor:	3° punto - CAT III

(* 1) Optional: Use of ISOMOTION technology for fixed or variable rate

Argentina

+54 3562 405015
R P N°1 Km. 7 1/2
CP 2421 - Morteros
Córdoba - Argentina

Brasil

+55 (14) 4105-0515
Rodovia Osny Mateus, km 111
São Judas Thadeu, Lençóis Paulista
SP, 18683-729 - Brasil



ttdobrasil.com

