

GROOVE 2010

SELECTIVE LAND PREPARATION



2 Prepares two seedbeds per pass.

SELECTIVE LAND PREPARATION FOR SUGARCANE

All-in-one land preparation equipment designed to improve the quality of sugarcane seedbed preparing only the area where the cane will be furrowed, planted and covered. Mounted to the three point of the tractor, without hydraulic connections, powered by the tractor PTO at 1000 RPM.



Technical features

- Power required: + 230 HP
- PTO: 1000 RPM - Splines: Ø 1 3/8" - Z21
- Weight: 2540 kg
- Working width: two seedbeds 1010 mm each



Every seedbed:

A - Cutting section with Five 22" straight notched discs, cutting trash up to 10 cms.

B - Two available subsoiler featuring:

1 - TWO (2) subsoilers working 30 to 45 cm deep with adjustable spacing between them for double line system (tramline).

2 - ONE (1) big subsoiler going up to 60 cm deep for single line row.

C - Rotocultivator soil refiner with rotating shaft and twenty-four (24) rotary hammers, which generate the loosening of the soil according to the client's needs, being able to adjust the granulometry of the clods by adjusting the rear gate of the rotary cultivator.

Fixation of the rotary cultivators to the chassis: connected by means of parallelogram arms that allow a better copying of the terrain during preparation

The equipment is modular, it allows working in individual or joint functions able to set up as a separate subsoiler from the rotary cultivators and use the two rotary cultivators connected to two tractors separately.

Espac.	Axle	Width	Height	Length
1,50	3,00	3,25	1,55	3,20
1,60	3,00	3,25	1,55	3,20
1,65	3,00	3,25	1,55	3,20
1,70	3,00	3,25	1,55	3,20
1,75	3,60	3,85	1,55	3,20
1,80	3,60	3,85	1,55	3,20
1,90	3,60	3,85	1,55	3,20
2,00	3,60	3,85	1,55	3,20



Argentina
+54 3562 405015
R P N°1 Km. 7 1/2
CP 2421 - Morteros
Córdoba - Argentina

Brasil
+55 (14) 4105-0515
Rodovia Osny Mateus, km 111
São Judas Thadeu, Lençóis Paulista
SP, 18683-729 - Brasil

